

Telehandler / Zoom Boom

Used Telehandler Torrance - Telehandlers go by many different names including a boom lift, telescopic handler, Cherry picker or teleporter. This industrial equipment is commonly used in a variety of industries including agriculture. Similar to a crane and a forklift as it has a boom allowing it to extend forwards and upwards. The operator can utilize a variety of attachments at the end of the articulating boom to complete different jobs. Different attachments such as a bucket, pallet forks, a muck grab or a winch can help the machine complete many jobs. The main telehandler attachment is the pallet forks. They allow the operator to transport loads to and from locations that are considered unreachable with a regular forklift. Telehandlers allow cargo pallets to be transported from trailers and placed on racking, rooftops or other difficult to reach locations. Often, high rooftop locations would need a crane although, telehandlers can accomplish these tasks much more efficiently. It isn't always practical or affordable to rely on a crane or secondary machinery to complete the job. A bucket grab or a bucket is the most common attachments for telehandlers within the agricultural sector. Transporting items from unreachable places that cannot use a backhoe loader or a wheeled loader is one of the main advantages of using a telehandler. For instance, these industrial machines can directly access a hopper or trailer with high sides; applications that would otherwise rely on a conveyor, loading ramp or similar equipment. Relying on one piece of equipment to complete a variety of jobs saves time, money and storage. Telehandler machines can work in conjunction with a crane jib. Numerous attachments can be utilized including power booms, grain buckets, dirt buckets and rotators. Agricultural models can be outfitted with power take-off and 3-point linkage, making the telehandler and exceptionally useful. Interestingly enough, the machines' main advantage is also its' biggest limitation. The boom acts as a lever when it extends or raises with heavy loads. Despite significant counterweights in the rear, the telehandler can be subject to instability at times, decreasing the lifting capacity as the working radius or distance between the center of the load and the front of the wheels increases. When a telehandler functions as a single boom loader (as opposed to twin arms) and carrying a heavy load, there can be a potential for weakness even in the best designs. A 5000 lb. capacity telehandler could lift 400 lbs. safely while fully extended with a retracted boom in conjunction with a low boom angle. This unit with a 5000 lb. lift capability and retracted boom could support as much as ten thousand pounds after the boom is raised seventy degrees. These machines are equipped with a load chart to help outline which tasks are safely possible. These charts take the boom height, angle and weight into account. Newer telehandler models rely on computers and sensors to monitor the machine. The operator cannot continue once the machine's limits have been reached. They are warned and cut off from accessing the control input. Front stabilizers that enhance the lifting capacity of the machine while stationary can make a huge difference. A stabilizing rotary joint between the upper and lower frames may be called a mobile crane that can use a bucket. Compact telehandler models are available in a variety of different weights, reach, sizes and boom designs. Telehandlers fall into the compact category if the unit weighs in at 11,000 lbs. or less. Compact models feature a two- stage boom design in comparison to the three or four boom design that is common with larger units. Compact models rely on a low pivot boom to facilitate better cab visibility as the operator transports loads. Obviously, the compact telehandler has narrower and tinier dimensions. Compact telehandlers have a reach capacity ranging between 13 to 20 feet with a lift capacity ranging from 5k to 7k pounds. These versatile machines make the compact telehandler extremely popular. It may be used as a tool carrier or a pick and place machine. It is commonly utilized in spaces that are tight and cramped. Residential services are often employed during framing and for jobs with height restrictions. These machines can facilitate internal building access. Compact units are popular in multi-story construction, nurseries, strip malls, landscaping, masonry, garage facilities and erecting steel among other applications. Telehandlers are employed by agri-business and farming applications to complete many jobs. Telehandlers come with crab steering or two or four-wheel drive

options. The unit can travel over longer ranges at higher speeds with two-wheel drive, making it ideal for moving throughout job sites. The 4-WD units are capable of having a tighter turning radius and can travel difficult terrain. Crab steering increases overall maneuvering and enables the front and back wheels to move 45 degrees to the left or the right. There are a variety of cab interior options available for compact telehandlers. There is a rollover protective cage to enhance safety on less expensive models. Higher models come with a heater, a completely enclosed cab, defroster and windshield wiper. Compact units feature spacious cab accommodations to keep operators totally comfortable. Additional features such as cup holders, air conditioning, tilt steering, suspension seats and satellite radio are all options. Many high-pressure hydraulics and high-flow auxiliary hydraulics operate the numerous attachments. These attachments increase the functions the machine is capable of. Ground engaging work is often completed by compact units. Adding a bucket attachment can make a compact telehandler transform into a mini excavator. Light-duty to heavy-duty buckets can be attached for transferring material, side-shifting and rotating fork carriages are relied on for pick and place situations, augers for drilling post holes or planting trees or pier supports, truss booms for extending reach, crane hooks, brooms for sweeping and more. Skid steer attachments are being manufactured for certain compact telehandler designs for even more versatility.